



通用型块状花纹

适用于铲运机，叉车，在港口、机场、工厂、仓库等环境下作业，具有良好的抗切割，耐磨损性能，宽厚的胎面花纹，提供了良好的接地及牵引性能，自洁性好，寿命长。

GENERAL PURPOSE BLOCK PATTERN TYRE SERIES

Suitable to scrapers and forklifts operating in areas like port, air port, factory and warehouse sites etc., with good cutting and wear resistances, wide and thick tread pattern provides good ground contact and traction, self-cleaning, long service life.

W-9A



W-9B



| 花纹编号 PATTERN | 轮胎规格 TIRE SIZE | 层级 PLY RATING | 标准轮辋 STANDARD RIM | 新胎充气后主要尺寸(MM) INFLATED SIZE OF NEW TIRE | | 最大负荷 (KG) MAXIMUM LOAD | 相应气压 (KPA) RELATIVE PRESSURE | 内胎 TT/TL |
|-----------------|-------------------|---------------------|----------------------|--|-------------------------------------|---------------------------------|---------------------------------------|-------------|
| | | | | 断面宽 SECTION WIDTH ±3.5% | 外直径 OVERALL DIAMETER ±1.5% | | | |
| W-9A | 5.00-8 | 8 | 3.50D | 137 | 470 | 1210 | 800 | TT |
| | 6.00-9 | 10 | 4.00E | 160 | 540 | 1625 | 850 | TT |
| | 7.00-9 | 10 | 5.00S | 190 | 590 | 2145 | 850 | TT |
| | 6.50-10 | 10 | 5.00F | 175 | 590 | 1775 | 775 | TT |
| | 7.00-12 | 12 | 5.00S | 190 | 676 | 2555 | 850 | TT |
| | 8.25-12 | 12 | 7.00 | 235 | 696 | 2850 | 790 | TT |
| | 7.50-15 | 12 | 6.00 | 215 | 808 | 2650 | 790 | TT |
| | 8.15-15 | 12 | 7.00 | 215 | 704 | 3230 | 840 | TT |
| W-9B | 8.25-15 | 12 | 6.50 | 235 | 840 | 3545 | 720 | TT |
| | | 14 | | | | 3700 | 800 | |
| | 9.00-20 | 18 | 7.00 | 262 | 1022 | 2700 | 740 | TT |
| | 10.00-20 | 18 | 7.50 | 280 | 1060 | 3000 | 740 | TT |
| | 12.00-20 | 20 | 8.50 | 320 | 1130 | 3700 | 740 | TT |